



WHITE 10mm LINES

White 10mm Lines allows you to effectively personalise your windows and glass partitions. It features a pattern composed of white 10 mm bands arranged horizontally and separated by 4 mm clear aspect bands.



Tintfit Window Films warranty

5 YEARS



Fire-resistance rating

M1



Storage from -5°C to +40°C

3 YEARS



REACH RoHS compliant

RESPECTED

TECHNICAL DATASHEET


Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

Ultraviolet transmission	NC %
Visible light transmission	- %
Reflection of external visible light	- %
Reflection of internal visible light	- %
Total solar energy rejected	- %
Total solar energy rejected 2	- %
Solar ratio :	
Solar energy reflection	- %
Solar energy absorption	- %
Solar energy transmission	- %
Reduction in Solar Glare	- %
g-value	-
u-value	-
Shading coefficient	NC
Installation type : Internal application	
Roll length	50 m
PET / PVC composition	PET
Thickness	40 μ

Colour : WHITE

CONSTRUCTION

1. High optical quality polyester with printed design
2. PS adhesive, glass polymerization within 15 days
3. Protection release liner, disposable after installation



MAINTENANCE INSTRUCTIONS

Soapy water solution, do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Non-contractual data, Tintfit Window Films reserves the right to modify the composition of its films at any time.

INSTALLATION ADVICE

Vertical installation and on standard glass surface*

Clear single pane	✓
Tinted single pane	✓
Reflective tinted single pane	✓
Clear double pane	✓
Tinted double pane	✓
Reflective tinted double pane	✓
Gas-filled double pane - Low E	✓
STADIP EXT. clear double pane	✓
STADIP INT. clear double pane	✓

✓ Yes ! Caution ✗ No

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².