



ULTIMA 40

Ultima 40 Film is a microperforated adhesive on which a high print quality can be produced. It is suitable for both automotive bodies and glass surfaces. Thanks to its structure, a maximum brightness is maintained (40% VLT). Its white printable side protects you from prying eyes and the black inside allows you to always have a perfect outward view.



Tintfit Window Films warranty

2 YEARS



Fire-resistance rating

M1



Storage from -5°C to +40°C

3 YEARS



REACH RoHS compliant

RESPECTED

TECHNICAL DATASHEET


Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

Ultraviolet transmission	50 %
Visible light transmission	40 %
Reflection of external visible light	50 %
Reflection of internal visible light	6 %
Total solar energy rejected	39 %
Total solar energy rejected 2*	44 %
Solar ratio :	
Solar energy reflection	40 %
Solar energy absorption	20 %
Solar energy transmission	40 %
Reduction in Solar Glare	42 %
g-value	0,44
u-value	-
Shading coefficient	0,5
Installation type : Internal application + External application	
Roll length	30,5 m
PET / PVC composition	PVC
Thickness	140 µ

Colour : WHITE

CONSTRUCTION

1. 100µ monomer PVC
2. Half Permanent Adhesive, allowing the "degassing" of the actual surface, and limits the adhesive transfer during removal
3. Protection release liner, disposable after installation



MAINTENANCE INSTRUCTIONS

Soapy water solution, do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

INSTALLATION ADVICE

Vertical installation and on standard glass surface**

Clear single pane	✓
Tinted single pane	✓
Reflective tinted single pane	✓
Clear double pane	✓
Tinted double pane	✓
Reflective tinted double pane	✓
Gas-filled double pane - Low E	✓
STADIP EXT. clear double pane	✓
STADIP INT. clear double pane	✓

✓ Yes ! Caution ✗ Not recommended

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².