

**NR OCEAN BLUE 24**

Applied to clear glass, the transparent Non Reflective Ocean Blue 24 bestows a blue tint to the glass without diminishing its transparent properties. It is the perfect way to enliven any interior glazing (such as partitions, shower screens, etc.) with a touch of colour.



Tintfit Window Films warranty

**5 YEARS**



Fire-resistance rating

**M1**



Storage from -5°C to +40°C

**3 YEARS**



REACH RoHS compliant

**RESPECTED**

**TECHNICAL DATASHEET**

Data calculated based on film applied to clear glass 3 mm thick (\*on double glazing 4-16-4)

Ultraviolet transmission	1 %
Visible light transmission	24 %
Reflection of external visible light	7 %
Reflection of internal visible light	7 %
Total solar energy rejected	32 %
Total solar energy rejected 2*	29 %
Solar ratio :	
Solar energy reflection	9 %
Solar energy absorption	47 %
Solar energy transmission	44 %
Reduction in Solar Glare	60 %
g-value	0,69
u-value	5.7
Shading coefficient	
Installation type : Internal application	
Roll length	30.5 m
PET / PVC composition	PET
Thickness	40 µ

Colour : BLUE

**CONSTRUCTION**


**INSTALLATION ADVICE**

Vertical installation and on standard glass surface\*\*

Clear single pane	✓
Tinted single pane	!
Reflective tinted single pane	✓
Clear double pane	!
Tinted double pane	!
Reflective tinted double pane	✓
Gas-filled double pane - Low E	!
STADIP EXT. clear double pane	!
STADIP INT. clear double pane	✗

✓ Yes    ! Caution    ✗ Not recommended

\*Recommendations provided on the basis of a glazed surface covering up to 2.5m<sup>2</sup>, contact us for definitive details or to obtain a thermal chock analysis report.



**MAINTENANCE INSTRUCTIONS**

Soapy water solution, do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

*Non-contractual data, Tintfit Window Films reserves the right to modify the composition of its films at any time.*