



Frost 18mm Lines decorative film allows you to effectively customize your windows and glass partitions. It features a pattern composed of 18 mm frosted bands arranged horizontally and separated by 6 mm clear aspect bands.

Certifications



Tintfit Warranty
5 years



Fire-Resistance Rating
M1



Storage From -5°C To +40°C
3 years



Reach Rohs Compliant
Respected



Widths Available
152cm

Construction

1. High optical quality polyester with printed design
2. PS adhesive, glass polymerization within 15 days
3. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution, do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Visible Light Transmission	0%
Reflection Of External Visible Light	0%
Reflection Of Internal Visible Light	0%
Solar Ratio :	
Solar Energy Reflection	0%
Solar Energy Absorption	0%
Solar Energy Transmission	0%
Reduction In Solar Glare	0%
Installation Type	Interior
Roll Length	30.5 metres
Film Composition	PET
Thickness	40µ
Colour From The Outside	FROSTED

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Laminated Ext. Clear Double Pane	✓
Laminated Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; Tintfit Window Films reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.