



Satin Frost Vinyl privacy films are designed to provide protection against the scrutiny of prying eyes. Whilst completely opalescent, the film still allows most natural light to pass through. With disposable paper liner for digital cutting.

Certifications



Tintfit Warranty
5 years



Fire-Resistance Rating
M1



Storage From -5°C To +40°C
3 years



Reach Rohs Compliant
Respected



Widths Available
76cm, 152cm

Construction

1. 95µ monomer PVC
2. Half Permanent Adhesive, allowing the "degassing" of the actual surface, and limits the adhesive transfer during removal
3. Disposable paper liner for digital cutting

Maintenance Instructions

Soapy water solution, do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Ultraviolet Transmission	5%
Visible Light Transmission	72%
Reflection Of External Visible Light	NC
Reflection Of Internal Visible Light	NC
Total Solar Energy Rejected	NC
Total Solar Energy Rejected 2*	NC
Solar Ratio :	
Solar Energy Reflection	NC
Solar Energy Absorption	NC
Solar Energy Transmission	NC
Reduction In Solar Glare	NC
G-Value	NC
U-Value	NC
Shading Coefficient	NC
Installation Type	Interior
Roll Length	50 metres
Film Composition	PVC
Thickness	95µ
Colour From The Outside	FROSTED

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Laminated Ext. Clear Double Pane	✓
Laminated Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; Tintfit Window Films reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.