



Enhance the elegance and privacy of your glass with our high quality Reeded Glass - 13mm Flutes decorative film. Our film replicates the timeless look of reeded glass, offering a stylish and functional solution for your home or office. Enjoy the beauty of diffused light while maintaining your desired level of privacy. Our reeded glass film is easy to install, durable and designed to last.

Certifications



Tintfit Warranty
5 years



Fire-Resistance Rating
M1



Storage From -5°C To +40°C
3 years



Reach Rohs Compliant
Respected



Widths Available
76cm, 152cm

Construction

1. High optical quality polyester with printed design
2. PS adhesive, glass polymerization within 15 days
3. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution, do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

| | |
|---------------------------|-------------|
| Solar Ratio : | |
| Solar Energy Reflection | |
| Solar Energy Absorption | |
| Solar Energy Transmission | |
| Installation Type | Interior |
| Roll Length | 50 metres |
| Film Composition | PET |
| Thickness | 70µ |
| Colour From The Outside | TRANSPARENT |

Installation Advice

Vertical position and standard glass surface*

| | |
|----------------------------------|---|
| Clear Single Pane | ✓ |
| Tinted Single Pane | ✓ |
| Reflective Tinted Single Pane | ✓ |
| Clear Double Pane | ✓ |
| Tinted Double Pane | ✓ |
| Reflective Tinted Double Pane | ✓ |
| Gas-Filled Double Pane - Low E | ✓ |
| Laminated Ext. Clear Double Pane | ✓ |
| Laminated Int. Clear Double Pane | ✓ |

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; Tintfit Window Films reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.