



With its well-appointed metallized design, High Performance Limo 05 automotive film combines discretion and privacy from prying eyes with technical efficiency by reflecting solar heat.

Certifications



Tintfit Warranty
Lifetime



Fire-Resistance Rating
M1



Storage From -5°C To +40°C
3 years



Reach Rohs Compliant
Respected



Widths Available
51cm, 76cm, 100cm, 152cm

Construction

1. Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
2. Dyed polyester without optical distortion, with anti IR metal particles deposit
3. Bonding adhesive
4. Dyed polyester without optical distortion,
5. PS adhesive, glass polymerization within 15 days
6. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution, do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Ultraviolet Transmission	1%
Visible Light Transmission	5%
Reflection Of External Visible Light	7%
Reflection Of Internal Visible Light	7%
Total Solar Energy Rejected	62%
Total Solar Energy Rejected 2*	57%
Solar Ratio :	
Solar Energy Reflection	11%
Solar Energy Absorption	72%
Solar Energy Transmission	17%
Reduction In Solar Glare	95%
G-Value	0.36
Shading Coefficient	-
Installation Type	Interior
Roll Length	30.5 metres
Film Composition	PET
Thickness	60µ
Colour From The Outside	BLACK

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✗
Reflective Tinted Single Pane	✗
Clear Double Pane	✗
Tinted Double Pane	✗
Reflective Tinted Double Pane	✗
Gas-Filled Double Pane - Low E	✗
Laminated Ext. Clear Double Pane	✗
Laminated Int. Clear Double Pane	✗

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; Tintfit Window Films reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.