



With its well-appointed metallized design, High Performance Light 35 automotive film combines discretion and privacy from prying eyes with technical efficiency by reflecting solar heat.

**Certifications**



**Tintfit Warranty**  
Lifetime



**Fire-Resistance Rating**  
M1



**Storage From -5°C To +40°C**  
3 years



**Reach Rohs Compliant**  
Respected



**Widths Available**  
51cm, 76cm, 100cm, 152cm

**Construction**

1. Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
2. Dyed polyester without optical distortion, with anti IR metal particles deposit
3. Bonding adhesive
4. Dyed polyester without optical distortion,
5. PS adhesive, glass polymerization within 15 days
6. Protection release liner, disposable after installation

**Maintenance Instructions**

Soapy water solution, do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

**Technical Datasheet**

Ultraviolet Transmission	1%
Visible Light Transmission	39%
Reflection Of External Visible Light	9%
Reflection Of Internal Visible Light	7%
Total Solar Energy Rejected	45%
Total Solar Energy Rejected 2*	42%
Solar Ratio :	
Solar Energy Reflection	10%
Solar Energy Absorption	51%
Solar Energy Transmission	39%
Reduction In Solar Glare	62%
G-Value	0.52
Shading Coefficient	-
Installation Type	Interior
Roll Length	30.5 metres
Film Composition	PET
Thickness	55µ
Colour From The Outside	BLACK

**Installation Advice**

Vertical position and standard glass surface\*

Clear Single Pane	✓
Tinted Single Pane	✗
Reflective Tinted Single Pane	✓
Clear Double Pane	!
Tinted Double Pane	✗
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✗
Laminated Ext. Clear Double Pane	✗
Laminated Int. Clear Double Pane	✗

✓ Yes ✗ Not Recommended ! Caution

\*Recommendations provided on the basis of a glazed surface covering up to 2.5m<sup>2</sup>.

The information on this data sheet is not binding; Tintfit Window Films reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.