



With a highly specific multi alloy metal composition, the Multiglass 35 film constitutes a significant barrier to solar absorption. It is highly effective in shielding against solar heat gain and further protects glazed surfaces from damage.

Certifications



Tintfit Warranty
10 years



Fire-Resistance Rating
M1



Storage From -5°C To +40°C
3 years



Reach Rohs Compliant
Respected



Widths Available
152cm

Construction

1. Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
2. High optical quality polyester, with anti IR metal particles deposit
3. Bonding adhesive
4. High optical quality polyester
5. PS adhesive, glass polymerization within 15 days
6. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution, do not clean for at least a month and do not apply any type of sticker or adhesive on the film. To prevent possible oxidation of the metal alloys, it is mandatory to use sealing varnish on the corners of the film, after installation.

Technical Datasheet

Ultraviolet Transmission	1%
Visible Light Transmission	47%
Reflection Of External Visible Light	29%
Reflection Of Internal Visible Light	28%
Total Solar Energy Rejected	66%
Total Solar Energy Rejected 2*	63%
Solar Ratio :	
Solar Energy Reflection	47%
Solar Energy Absorption	25%
Solar Energy Transmission	28%
Reduction In Solar Glare	52%
G-Value	0.36
U-Value	4.9
Rejected Infrared (760-2500 Nm)	+/-80%
Shading Coefficient	0.4
Installation Type	Interior
Roll Length	30.5 metres
Film Composition	PET
Thickness	55µ
Colour From The Outside	CHAMPAGNE

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Laminated Ext. Clear Double Pane	✓
Laminated Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; Tintfit Window Films reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.