








Low E Silver 20 thermal insulation films reduce excess heat gain through glass in summer and also limit heat loss in winter. Significant savings in heating and air-conditioning costs can be made once this film is applied to windows, rapidly offsetting the initial cost of purchase and installation.

Certifications

-  **Tintfit Warranty**
6 years
-  **Fire-Resistance Rating**
M1
-  **Storage From -5°C To +40°C**
3 years
-  **Reach Rohs Compliant**
Respected
-  **Widths Available**
152cm

Construction

1. Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
2. High optical quality polyester, with anti IR metal particles deposit
3. Bonding adhesive
4. High optical quality polyester
5. PS adhesive, glass polymerization within 15 days
6. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution, do not clean for at least a month and do not apply any type of sticker or adhesive on the film. To prevent a possible oxidation of the metal alloys, it is mandatory to use sealing varnish on the corners of the film, after installation.

Technical Datasheet

Ultraviolet Transmission	1%
Visible Light Transmission	15%
Reflection Of External Visible Light	53%
Reflection Of Internal Visible Light	61%
Total Solar Energy Rejected	82%
Total Solar Energy Rejected 2*	86%
Solar Ratio :	
Solar Energy Reflection	63%
Solar Energy Absorption	25%
Solar Energy Transmission	15%
Reduction In Solar Glare	83%
G-Value	0.18
U-Value	3.8
Heat Loss Reduction (Winter)	34%
Shading Coefficient	0.62
Installation Type	Interior
Roll Length	30.5 metres
Film Composition	PET
Thickness	50µ
Colour From The Outside	SILVER

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	!
Tinted Double Pane	✗
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✗
Laminated Ext. Clear Double Pane	!
Laminated Int. Clear Double Pane	✗

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; Tintfit Window Films reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.