








Carefully applied to any kind of glazing, Neutral UV 60 films are highly effective at absorbing ultraviolet rays and light originating from the Sun and the Moon. This film will protect items and furnishings exposed to Sun or Moon light from fading and premature ageing.

Certifications

-  **Tintfit Warranty**
10 years
-  **Fire-Resistance Rating**
M1
-  **Storage From -5°C To +40°C**
3 years
-  **Reach Rohs Compliant**
Respected
-  **Widths Available**
152cm

Construction

1. Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
2. High optical quality polyester, with anti IR metal particles deposit
3. Bonding adhesive
4. High optical quality polyester
5. PS adhesive, glass polymerization within 15 days
6. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution, do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Ultraviolet Transmission	0.5%
Visible Light Transmission	66%
Reflection Of External Visible Light	11%
Reflection Of Internal Visible Light	11%
Total Solar Energy Rejected	42%
Total Solar Energy Rejected 2*	40%
Solar Ratio :	
Solar Energy Reflection	18%
Solar Energy Absorption	26%
Solar Energy Transmission	56%
Reduction In Solar Glare	28%
G-Value	0.59
U-Value	5.8
Shading Coefficient	0.7
Installation Type	Interior
Roll Length	30.5 metres
Film Composition	PET
Thickness	50µ
Colour From The Outside	LIGHT GREY

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Laminated Ext. Clear Double Pane	✓
Laminated Int. Clear Double Pane	!

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; Tintfit Window Films reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.