



Opal Frost Vinyl privacy films are designed to provide protection against the scrutiny of prying eyes. Whilst completely opalescent, the film still allows most natural light to pass through. With disposable paper liner for digital cutting.

**Certifications**



**Tintfit Warranty**  
5 years



**Fire-Resistance Rating**  
M1



**Storage From -5°C To +40°C**  
3 years



**Reach Rohs Compliant**  
Respected



**Widths Available**  
76cm, 152cm

**Construction**

1. 100µ Frosted monomer PVC
2. Half Permanent Adhesive, allowing the "degassing" of the actual surface, and limits the adhesive transfer during removal
3. Disposable paper liner for digital cutting

**Maintenance Instructions**

Soapy water solution, do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

**Technical Datasheet**

Ultraviolet Transmission	>25%
Visible Light Transmission	76%
Reflection Of External Visible Light	15%
Reflection Of Internal Visible Light	15%
Total Solar Energy Rejected	18%
Total Solar Energy Rejected 2*	19%
Solar Ratio :	
Solar Energy Reflection	10%
Solar Energy Absorption	17%
Solar Energy Transmission	73%
Reduction In Solar Glare	20%
G-Value	0.77
U-Value	5.6
Shading Coefficient	
Installation Type	Interior
Roll Length	30.5 metres
Film Composition	PVC
Thickness	100µ
Colour From The Outside	FROSTED

**Installation Advice**

Vertical position and standard glass surface\*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Laminated Ext. Clear Double Pane	✓
Laminated Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

\*Recommendations provided on the basis of a glazed surface covering up to 2.5m<sup>2</sup>.

The information on this data sheet is not binding; Tintfit Window Films reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.