








Opal Frost Static privacy films are designed to provide protection against the scrutiny of prying eyes. Whilst completely opalescent, the film still allows most natural light to pass through. With disposable plastic liner. In addition, this "static" version is easy to install.

Certifications

-  **Tintfit Warranty**
2 years
-  **Fire-Resistance Rating**
M1
-  **Storage From -5°C To +40°C**
3 years
-  **Reach Rohs Compliant**
Respected
-  **Widths Available**
152cm

Construction

1. 100µ Frosted monomer PVC
2. Protection liner, disposable after the installation

Maintenance Instructions

Soapy water solution, do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Ultraviolet Transmission	>25%
Visible Light Transmission	76%
Reflection Of External Visible Light	15%
Reflection Of Internal Visible Light	15%
Total Solar Energy Rejected	18%
Total Solar Energy Rejected 2*	19%
Solar Ratio :	
Solar Energy Reflection	10%
Solar Energy Absorption	17%
Solar Energy Transmission	73%
Reduction In Solar Glare	20%
G-Value	0.77
U-Value	5.6
Installation Type	Interior
Roll Length	20 metres
Film Composition	PVC
Thickness	100µ
Colour From The Outside	FROSTED

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Laminated Ext. Clear Double Pane	✓
Laminated Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; Tintfit Window Films reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.