








External Dusted Frost Vinyl privacy films are designed to provide protection against the scrutiny of prying eyes. Whilst completely opalescent, the film still allows most natural light to pass through.

Certifications

-  **Tintfit Warranty**
5 years
-  **Fire-Resistance Rating**
M1
-  **Storage From -5°C To +40°C**
3 years
-  **Reach Rohs Compliant**
Respected
-  **Widths Available**
152cm

Construction

1. 75µ "cast" polymer PVC
2. Half Permanent Adhesive, allowing the "degassing" of the actual surface, and limits the adhesive transfer during removal
3. Paper release liner allowing digital cutting

Maintenance Instructions

Soapy water solution, do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Ultraviolet Transmission	>25%
Visible Light Transmission	60%
Reflection Of External Visible Light	18%
Reflection Of Internal Visible Light	18%
Total Solar Energy Rejected	28%
Total Solar Energy Rejected 2*	29%
Solar Ratio :	
Solar Energy Reflection	18%
Solar Energy Absorption	15%
Solar Energy Transmission	67%
Reduction In Solar Glare	40%
G-Value	0.71
U-Value	5.6
Shading Coefficient	
Installation Type	Exterior
Roll Length	50 metres
Film Composition	PVC
Thickness	75µ
Colour From The Outside	FROSTED

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Laminated Ext. Clear Double Pane	✓
Laminated Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; Tintfit Window Films reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.